

# Air-Operated Double Diaphragm Pumps (AODD)

## Drum Pumps



### Features

- Available in a range of sizes and materials suitable for pumping directly from 55 gallon drums
- For the safe clean and efficient transfer of all kinds of liquids including; Corrosive Chemicals, Oils, Lubricants Waste liquids, Solvents, Paints, Inks, Diesel, and other Fuels
- Available with 1/4" 3/8" 1/2" 3/4" and 1" pump connections
- Available in; Pure PP, GFRPP, Conductive PP, PVDF, PTFE, Aluminium, SUS & Electro Polished SUS
- Max Flow Rate up to: 58 gpm
- Max Particle Size up to: 6.5mm
- Max Liquid Discharge Pressure: 100 psi



**3/8" Stainless Steel Drum Pump**  
6 gpm Max Flow Rate



**Drum Bung Adapter**  
(SUS)



**1" Stainless Steel Drum Pump**  
58 gpm Max Flow Rate



**1/2" Polypropylene Drum Pump**  
15 gpm Max Flow Rate



**1/4" Stainless Steel Drum Pump**  
3 gpm Max Flow Rate

### Air-Operated Double Diaphragm (AODD) Pump Capabilities

Self Priming  
Can Run Dry  
Can Run Deadhead  
Variable Flow Rates

Variable Discharge Pressures  
Transfer Liquid Slurries  
Can Handle Hard Abrasive Solids  
Can Handle a Wide Variety of Liquids

Explosion Proof / Intrinsically Safe  
Portable & Easy to Use  
Can Pump Shear Sensitive Fluids  
Transfer Viscous Fluids



Five Boynton Road, Holliston, MA 01746 USA  
Tel: 508-429-1440 / service@iwaki-america.com / www.iwaki-air.com

IALT00458 Oct 2020